

| 型式 | 伝熱面積 m ² | A | B | C | Dφ | E | F | H | 重量kg |
|------------|------------------------|-------|-------|-----|-------|------|-----|-----|------|
| HTF-40-05 | 0.21 | 600 | 400 | | | | | | 8 |
| HTF-40 | 0.4 | 1,100 | 900 | 100 | 48.6 | 40A | 25A | 110 | 10 |
| HTF-40-20 | 0.8 | 2,100 | 1,900 | | | | | | 14 |
| HTF-50-05 | 0.4 | 600 | 400 | | | | | | 11 |
| HTF-50 | 0.8 | 1,100 | 900 | 100 | 60.5 | 50A | 32A | 110 | 13 |
| HTF-50-20 | 1.6 | 2,100 | 1,900 | | | | | | 18 |
| HTF-65-05 | 0.6 | 600 | 400 | | | | | | 15 |
| HTF-65 | 1.2 | 1,100 | 900 | 100 | 76.3 | 65A | 40A | 110 | 19 |
| HTF-65-20 | 2.4 | 2,100 | 1,900 | | | | | | 27 |
| HTF-80-05 | 0.76 | 600 | 400 | | | | | | 17 |
| HTF-80 | 1.5 | 1,100 | 900 | 100 | 89.1 | 80A | 50A | 120 | 22 |
| HTF-80-20 | 3 | 2,100 | 1,900 | | | | | | 33 |
| HTF-100-05 | 1.4 | 600 | 400 | | | | | | 21 |
| HTF-100 | 2.9 | 1,100 | 900 | 100 | 114.3 | 100A | 50A | 150 | 29 |
| HTF-100-20 | 5.9 | 2,100 | 1,900 | | | | | | 45 |
| HTF-125-05 | 2.4 | 600 | 400 | | | | | | 30 |
| HTF-125 | 4.8 | 1,100 | 900 | 100 | 139.8 | 125A | 65A | 180 | 41 |
| HTF-125-20 | 9.6 | 2,100 | 1,900 | | | | | | 63 |
| HTF-150-05 | 3.25 | 600 | 350 | | | | | | 37 |
| HTF-150 | 6.5 | 1,100 | 850 | 125 | 165.2 | 150A | 80A | 210 | 52 |
| HTF-150-20 | 13 | 2,100 | 1,850 | | | | | | 80 |
| HTF-200-05 | 6.05 | 630 | 350 | | | | | | 53 |
| HTF-200 | 12.1 | 1,130 | 850 | 140 | 216.3 | 200A | 80A | 210 | 80 |
| HTF-200-20 | 24.2 | 2,130 | 1,850 | | | | | | 130 |